

# MATERIAL SAFETY DATA SHEET

NOT classified as hazardous according to criteria of WorkSafe Australia

## HR50 Polyol - Part A

### IDENTIFICATION

Product Name: Erathane HR50 Polyol  
Use: Polyurethane foam curative  
UN Number: None allocated  
Proper Shipping Name: None allocated  
Dangerous Goods Class: None allocated  
Subsidiary risk: None allocated  
Packing Group: None allocated  
Hazchem Code: None allocated

### PHYSICAL PROPERTIES

Appearance: Viscous white liquid  
Boiling Point /°C: Decomposes at elevated temperatures Vapour Pressure  
/mmHg at 25°C: Nil  
Specific gravity @ 20°C: 1.03  
Flashpoint /°C: >180°C (Pensky martens closed cup)  
Flammability limits: Not determined  
Solubility in Water /mgL<sup>-1</sup>: Slightly soluble

### Other Properties

May decompose in heat or fire releasing products of possible greater hazard.

### INGREDIENTS

<u>SUBSTANCE NAME</u>	<u>Proportion</u>	<u>CAS Number</u>
POLYETHER POLYOL - NON HAZARDOUS	Greater than 60%	Mixture

### HEALTH HAZARD INFORMATION

#### ACUTE HEALTH EFFECTS

Not classified as hazardous according to the criteria of WorkSafe Australia.

**Hazard Category: None**

#### ACUTE HEALTH EFFECTS

##### Swallowed:

May cause irritation to mouth, throat and stomach with effects including mucous build up, irritation to the tongue and lips and pains in the stomach.

##### Eye:

May cause irritation to the eyes, with effects including: tearing, pain, and stinging and blurred vision.

##### Skin:

May cause irritation to the skin, with effects including: Redness and itchiness.

##### Inhaled:

May cause irritation to the nose, throat and respiratory system with effects including: Dizziness, headache and possible confusion.

# MATERIAL SAFETY DATA SHEET

NOT classified as hazardous according to criteria of WorkSafe Australia

## HR50 Polyol - Part A

### HEALTH HAZARD INFORMATION (cont.)

#### Chronic:

#### FIRST AID

##### Swallowed:

If swallowed, DO NOT induce vomiting, unless instructed to do so by trained health professional. Transport to hospital or doctor.

##### Eye:

If material is splashed into eyes, immediately, flush with plenty of water for 15 minutes, ensuring eyelids are held open. If irritation persists transport to hospital or doctor.

##### Skin:

If material is splashed onto the skin, remove any contaminated clothing and wash skin thoroughly with water and soap if available.

If irritation persists transport to hospital or doctor.

##### Inhaled:

Open all doors, windows and/or vents. Move victim to fresh air. Apply resuscitation if victim is not breathing - If trained personnel available administer oxygen if breathing is difficult.

##### First Aid Facilities:

Eye wash fountain, safety shower and normal washroom facilities.

##### Advice to Doctor:

Treat symptomatically.

### PRECAUTIONS FOR USE

#### Exposure Standards

Polyether Polyol – Non Hazardous

No exposure details available.

#### Engineering Controls

Maintain adequate ventilation at all times. In most circumstances natural ventilation systems are adequate unless the material is heated, reacted or otherwise changed in some type of chemical reaction, then the use of a local exhaust ventilation system is recommended.

#### Personal Protection Equipment

CLOTHING: PVC or natural rubber apron or splash suit.

GLOVES: PVC or natural rubber.

EYES: Chemical goggles or face shield to protect eyes.

RESPIRATORY PROTECTION: Avoid breathing of vapours. Select and use respirators in accordance with AS/NZS 1715/1716. When vapours exceed the exposure standards then the use an atmosphere-supplied, positive pressure demand self-contained or airline breathing apparatus supplied air respirator complying with the requirements of AS/NZS 1715 is recommended. Filter capacity and respirator type depends on exposure levels. If entering spaces where the airborne concentration of a contaminant is unknown then the use of a Self-contained breathing apparatus (SCBA) with positive pressure air supply complying with AS/NZS 1715 / 1716, or any other acceptable International Standard is recommended.

# MATERIAL SAFETY DATA SHEET

NOT classified as hazardous according to criteria of WorkSafe Australia

## HR50 Polyol - Part A

### SAFE HANDLING INFORMATION

Store in a cool place and out of direct sunlight. Store away from sources of heat or ignition. Store away from oxidizing agents. Keep containers closed, when not using the product. Store in original packages as approved by manufacturer.

#### Transport

UN Number:	None allocated
Proper Shipping Name:	None allocated
Dangerous Goods Class:	None allocated
Subsidiary risk:	None allocated
Packing Group:	None allocated
Hazchem Code:	None allocated

Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code) 6th Edition. Not classified as a Dangerous Good according to the UN, DOT (US), IACO (IATA) or IMO (IMDG).

Non Dangerous Good according to the ADG Code (6th Edition).

#### Spills

Ventilate area. Remove all unnecessary personnel from spill area. Wear protective equipment to prevent skin and eye contact, as outlined under personal protection in this MSDS. Contain using sand or soil - prevent run off into drains and waterways. Use absorbent (soil, sand, vermiculite or other inert material). Do not use sawdust. Collect and seal in properly labeled containers for disposal. Disposal For disposal information contact the State Land Waste Management Authority or the Environmental Protection Agency.

#### Disposal

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to an approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

#### Fire

##### Fire/Explosion Hazard

If safe to do so, move undamaged containers from fire area.

Hazardous Decomposition Products: Decomposes on heating emitting soot, smoke and decomposition products. Fire Fighting Procedures Fire fighters to wear Self-contained breathing apparatus (SCBA) in confined spaces, in oxygen deficient atmospheres or if exposed to products of decomposition. Full protective clothing is also recommended. Extinguishing Media: Use extinguishing media suitable for surrounding fire situation.

#### Flammability

This material is not a flammable or combustible liquid.

### OTHER INFORMATION

#### RISK PHRASES

#### SAFETY PHRASES

S24/25 Avoid contact with skin and eyes.

#### Ecotoxicity

This product should not be disposed of in drains, waterways or sewers.

### OTHER INFORMATION (Cont.)

# MATERIAL SAFETY DATA SHEET

NOT classified as hazardous according to criteria of WorkSafe Australia

## HR50 Polyol - Part A

**Poison Schedule**

**Poison Schedule: S6**

### CONTACT POINT

Contact Point

Technical Manager 03 9579 2044.

**Disclaimer** The information herein is to the best of our knowledge, correct and complete. It describes the safety requirements for this product and should not be construed as guaranteeing specific properties. Since methods and conditions are beyond our control we do not accept liability for any damages resulting from the use of or reliance on, this information in inappropriate contexts.