



Moulding and Casting Materials Sales: +61 03 9579 2044 sales@solidsolutions.com.au
19 Ardena Crt, East Bentleigh Admin: +61 03 9579 1889 admin@solidsolutions.com.au
PO Box 142, Vic, 3165 Fax: +61 03 9579 0573 www.solidsolutions.com.au

British United Industries (Vic) Pty Ltd ATF Byrne Hughes Family Business Trust Trading as A to Z Solid Solutions ABN 46 977 073 014 ACN 006 303 591

EPOXY CAST 303

Epoxy Cast 303 is a two component epoxy resin system designed to provide a tough, durable high gloss coating.

It can be poured to provide a glass like finish on most materials.

Typical Properties - Application and Handling

Colour Resin (Part A)	-	Clear Liquid
Colour Hardener (Part B)	-	Clear Liquid
Mix Ratio	-	2 parts Part A
	-	1 part Part B by volume
Working Time at 20°C	-	30 minutes
(100gm mix)		
Cure Time	-	3 - 4 hours at 40°C.

Mixing Instructions.

Measure out two parts Part A - one part Part B using a measuring cup or graduated container. Mix thoroughly. Be sure to scrape the sides and bottom of the container, during mixing.

Application Instructions.

Pour or apply by a syringe on to the object to be coated.

If bubbles are present in the coating film, these may be removed by gently blowing over the item. Large bubbles may also be broken with a pin.